



10FH500

10" - 500 W - 96 dB

NOMINAL SPECIFICATIONS

Nominal Diameter	250 mm (10 in)
Overall Diameter	261 mm (10.28 in)
Bolt Circle Diameter	246 mm (9.69 in)
Baffle Cutout Diameter	232 mm (9.13 in)
Depth	141.3 mm (5.56 in)
Flange and gasket Thickness	12.5 mm (0.49 in)
Net Weight	3.4 kg (7.5 lb)
Shipping Box	294 x 290 x 203 mm
(Single Carton Box)	(11.6 x 11.4 x 7.8 in)
Shipping Weight	4 kg (8.8 lb)

TECHNICAL PARAMETERS

Nominal Impedance	4 Ω
Minimum Impedance	4 Ω
AES Power Handling (1)	500 W
Maximum Power Handling (4)	1000 W
Sensitivity (1W/1m)	96 dB
Frequency Range	60 ÷ 4000 Hz
Voice Coil Diameter	77 mm (3 in)
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	18 mm (0.71 in)
Magnetic Gap Depth	10.5 mm (0.41 in)
Flux Density	1.2 T
Magnet	Neodymium Slug
Basket Material	Aluminum
Demodulation	No
Cone Surround (5)	Triple Roll
NET Air Volume filled by Loudspeaker	1.6 dm ³ (0.057 ft ³)
Spider Profile	1x constant height waves

THIELE & SMALL PARAMETERS

Fs	60 Hz
Re	3.3 Ω
Qes	0.26
Qms	6.2
Qts	0.25
Vas	21.4 dm ³ (0.76 ft ³)
Sd	328 cm ² (50.84 in ²)
Xmax (2)	7.25 mm
Xdamage (3)	12.5 mm
Mms	50.1 g
Bl	15.5 N/A
Le	0.64 mH
Mmd	46.7 g
Cms	0.14 mm/N
Rms	3 kg/s
η _o (Eta Zero)	1.73 %
EBP	231 Hz

NOTE:

- 2 Hours Test According to AES 2-1984 Rev. 2003
 - Xmax = [(Winding Depth - magnetic gap depth)/2] + (magnetic gap depth / 3)
 - Maximum excursion before permanent damage
 - Maximum power is defined as 3dB greater than nominal power
 - Treated Polycotton
- PATENT IT2006/000327

