



# 10PR310

10" - 300 W - 97 dB

## NOMINAL SPECIFICATIONS

Nominal Diameter	250 mm (10 in)
Overall Diameter	261 mm (10.28 in)
Bolt Circle Diameter	246 mm (9.69 in)
Baffle Cutout Diameter	230 mm (9.06 in)
Depth	109 mm (4.29 in)
Flange and gasket Thickness	12 mm (0.47 in)
<b>Net Weight</b>	<b>4.1 kg (9.0 lb)</b>
Shipping Box	282 x 280 x 140 mm
(Single Carton Box)	(11.1 x 11.0 x 5.5 in)
Shipping Weight	4.7 kg (10.4 lb)

## TECHNICAL PARAMETERS

Nominal Impedance	4 Ω
Minimum Impedance	4 Ω
AES Power Handling (1)	300 W
<b>Maximum Power Handling (4)</b>	<b>600 W</b>
<b>Sensitivity (1W/1m)</b>	<b>97 dB</b>
Frequency Range	60 ÷ 4000 Hz
<b>Voice Coil Diameter</b>	<b>65 mm (2.56 in)</b>
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	12.5 mm (0.49 in)
<b>Magnetic Gap Depth</b>	<b>8 mm (0.31 in)</b>
Flux Density	1.2 T
<b>Magnet</b>	<b>Ferrite Ring</b>
Basket Material	Aluminum
Demodulation	No
Cone Surround (5)	M-Roll
NET Air Volume filled by Loudspeaker	1.3 dm <sup>3</sup> (0.046 ft <sup>3</sup> )
Spider Profile	1x variable height waves

## THIELE & SMALL PARAMETERS

Fs	55 Hz
Re	3.3 Ω
Qes	0.32
Qms	7.4
Qts	0.29
Vas	35.2 dm <sup>3</sup> (1.24 ft <sup>3</sup> )
Sd	322 cm <sup>2</sup> (49.91 in <sup>2</sup> )
Xmax (2)	4.92 mm
Xdamage (3)	15.25 mm
Mms	35.1 g
Bl	11.5 N/A
Le	0.45 mH
Mmd	32.1 g
Cms	0.24 mm/N
Rms	1.64 kg/s
η <sub>o</sub> (Eta Zero)	1.88 %
EBP	172 Hz

### NOTE:

- 2 Hours Test According to AES 2-1984 Rev. 2003
- $X_{max} = [(Winding\ Depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth / 3)$
- Maximum excursion before permanent damage
- Maximum power is defined as 3dB greater than nominal power
- Treated Polycotton

