



18XL1600

18" - 1600 W - 98 dB

NOMINAL SPECIFICATIONS

Nominal Diameter	460 mm (18 in)
Overall Diameter	460 mm (18.11 in)
Bolt Circle Diameter	440 mm (17.32 in)
Baffle Cutout Diameter	422 mm (16.61 in)
Depth	231 mm (9.09 in)
Flange and gasket Thickness	14 mm (0.55 in)
Net Weight	12.2 kg (26.9 lb)
Shipping Box	490 x 485 x 275 mm
(Single Carton Box)	(19.3 x 19.1 x 10.8 in)
Shipping Weight	13.7 kg (30.2 lb)

TECHNICAL PARAMETERS

Nominal Impedance	4 Ω
Minimum Impedance	4.4 Ω
AES Power Handling (1)	1600 W
Maximum Power Handling (4)	3200 W
Sensitivity (1W/1m)	98 dB
Frequency Range	30 ÷ 1500 Hz
Voice Coil Diameter	100 mm (4 in)
Winding Material	Cu
Former Material	Glass Fiber
Winding Depth	31 mm (1.22 in)
Magnetic Gap Depth	15.5 mm (0.61 in)
Flux Density	0.98 T
Magnet	Neodymium Slug Crown
Basket Material	Aluminum
Demodulation	Triple Al Dem. Ring
Cone Surround (5)	Triple Roll
NET Air Volume filled by Loudspeaker	7.3 dm ³ (0.258 ft ³)
Spider Profile	2x non-adjacent symmetrical constant height waves

THIELE & SMALL PARAMETERS

Fs	32 Hz
Re	3 Ω
Qes	0.32
Qms	8.6
Qts	0.31
Vas	175.7 dm ³ (6.20 ft ³)
Sd	1124 cm ² (174.22 in ²)
Xmax (2)	12.92 mm
Xdamage (3)	28 mm
Mms	252.3 g
Bl	21.7 N/A
Le	1.17 mH
Mmd	229.5 g
Cms	0.10 mm/N
Rms	5.91 kg/s
γ _e (Eta Zero)	1.73 %
EBP	100 Hz

NOTE:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
 (2) Xmax = [(Winding Depth - magnetic gap depth)/2] + (magnetic gap depth / 3)
 (3) Maximum excursion before permanent damage
 (4) Maximum power is defined as 3dB greater than nominal power
 (5) Treated Polycotton
 PATENT PENDING

