



DE820TN

HF Drivers - 1.4 Inches

220 W continuous program power capacity
1.4' horn throat diameter
75 mm (3 in) aluminium voice coil
Titanium diaphragm
500 - 18000 Hz response
107 dB sensitivity
Neodymium magnet assembly with shorting copper cap

Specification

Throat Diameter	36 mm (1.4 in)
Nominal Impedance	8 ohm
Minimum Impedance	8.5 ohm
Continuous Power Handling	220 W
Nominal Power Handling (AES)	110 W
Sensitivity (1W/1m)	107 dB
Frequency Range	0.5 - 18 kHz
Recommended Crossover	1.2 kHz
Voice Coil Diameter	75 mm (3 in)
Winding Material	Aluminium
Inductance	0.14 mH
Diaphragm material	Titanium
Flux Density	1.85 T
Magnet Material	Neodymium Ring

Mounting & Shipping

Shipping Box (4 units)	300x160x180 mm (11.8x6.3x7.5 in)
Replacement Diaphragm	MMD3CTN8M

Mounting & Shipping

Overall Diameter	124 mm (4.9 in)
Depth	55 mm (2.2 in)
Net Weight	2.3 kg (5.1 lb)
Shipping Weight (4 units)	9.8 kg (21.5 lb)