XR2064C

Constant Coverage HF Horn

KeyFeatures

- 2 inch throat entry
- High damping composite structure Uniform on-axis and off-axis frequency response
- 60° x 40° horizontal and vertical constant coverage
- Very low distortion at high sound pressure
- Optimized weight thanks to composite material structure

Description

The XR2064C is a constant directivity 2 inch horn. The XR2064C has been developed to reach the optimum performance when coupled to 2 inch exit Eighteen Sound high frequency compression drivers.

All XR series horns have been designed in order to reach smooth driver frequency response, to maintain constant coverage and directivity and eliminating the midrange narrowing and high frequency beaming problems common of many similar horns on the market.

The XR2064C horn maintains nominal 60° Horizontal x 40° Vertical pattern control. It provides consistent on-axis and off-axis frequency response from 1.2kHz to 16kHz in both horizontal and vertical planes. Horn directivity is constant down to 1.2kHz.

Models

| Model | Code | Information |
|---------|------------|-------------|
| XR2064C | 0422064C00 | |



General Specifications

| Contra Opecanicationic | | |
|----------------------------|---|--|
| - | | HORIZONTAL BEAMWIDTH, RED PLOT - VERTICAL BEAMWIDTH, BLUE PLOT - A |
| Throat Diameter | 50 mm (2 in) | |
| Horizontal Coverage (-6dB) | 60° (10 ÷ -6) average range (1,6kHz - 12,5kHz) | |
| Vertical Coverage (-6 dB) | 40° (30 ÷ 0) average range (1,6kHz - 12,5kHz) | |
| Directivity Index | 11 dB (1.8 ÷ - 2.6) average range (1,6kHz - 12,5kHz) | DIRECTIVITY INDEX - B |
| Usable Frequency Range | Above 800 Hz | Horizontal and Vertical Polar Directivity Map |
| Recomm. Cross.Frequency | 800 Hz or more | , |
| Sensitivity | 110 dB | |
| Frequency Range | 800 Hz - 18KHz | |
| Material | Composite material | |
| | | |

Thiele Small Parameters

Mounting information

| Mouth Height | 270 mm (10,6 in) |
|---------------------------|------------------|
| Mouth Width | 270 mm (10,6 in) |
| Depth | 200 mm (7,9 in) |
| Mouth Mounting Dimensions | 8 ø 6 holes |
| Net weight | 1.8 Kg (3.97 lb) |

Notes

1) Sensitivity is measured at 1W input on ND2080 rated impedance at 1m on axis from the mouth of the horn, averaged between 1kHz and 4 kHz.

HORIZONTAL 1/3 OCTAVE POLAR PLOTS

VERTICAL 1/3 OCTAVE POLAR PLOTS

