

## P12N8Ω Code ZJ06040 12" 50W

**HIGHS: OVERDRIVE:** LOWS: MIDS: **Bright** Aggressive Edgy Loose

oudspeakers

## Sound Features:

## **Guitarist Description:**

Very warm and full bodied tone with powerful mid-bite and sparkling highs. When presented with overdrive distortion, it displays a bright and colorful crunch.




Specifications					
Nominal Diameter	307	mm (12")			
Nominal Impedance	8	Ω			
Rated Power AES <sup>(1)</sup>	50	W			
Continuous Program Power <sup>(2)</sup>	100	W			
Sensitivity @ 1W/1m	97.5	dB			
Voice Coil Diameter	38	mm			
Voice Coil Winding Depth	10	mm			
Magnetic Gap Depth	8	mm			
Flux Density	1.26	Т			
Magnet Weight	826	g			
Net Weight	3.1	kg			

Thiele & Small Parameters (3)				
Re	6.03 Ω	Fs	90.0 Hz	
Qms	4.36	Mms	30.9 g	
Qts	0.77	BxI	10.62 Tm	
Cms	101 μm/N	Sd	490.9 cm <sup>2</sup>	
Vas	34.6 I	Le (1kHz)	0.87 mH	

Constructive Characteristics			
Magnet	AINiCo		
Basket Material	Pressed Sheet Steel		
Voice Coil Winding Material	Copper		
Voice Coil Former Material	Kapton		
Cone Material	Paper		
Surround Treatment	No		
Surround Material	Paper - Integrated		
Dust Dome Material	Solid Paper		

n° 8 holes Ø 6.5



SICA Altoparlanti s.r.l. - ITALY - website: www.sica.it - E-mail: lab@sica.it - Tel. +39-071-7958072 - Fax +39-071-7959006